



Explanations see practical informations on page 6 and 84!

## SLS - FUME CUPBOARD UNDERBENCH CABINETS AS PER TRGS 526 / DGUV

### For storage of acids and alkalis

- ◆ Body made from HPL-coated sheets - particularly impact, scratch and abrasion proof
- ◆ Color RAL 7035 - light grey
- ◆ Inner body / inner fittings completely made from corrosion-proof components
- ◆ Doors with separate cylinder locks
- ◆ Marking according to ASR A1.3
- ◆ DN 80 ventilation connection for exhaust air extraction in the back wall
- ◆ Supply air by ventilation grille
- ◆ SLS-AUS 1100 with center partition wall

**storeLAB**  
by LACOR



**SLS-AUS 1100,**  
**Article no. B80-2823-A**

### With inner fittings:

- ◆ 1 (SLS-AUS 600) pull-out shelf, or 2 pull-out shelves, with end stop, arranged side by side
  - Max. load 20 kg / shelf
  - Front edge of shelves in attractive solid wood design
  - PE sump tray (sump capacity 20 liters) on shelf secured against slipping - easy to remove



**SLS-AUS 600,**  
**Article no. B80-2859-A**

Model	SLS-AUS 600	SLS-AUS 1100
External dimension W x D x H (mm)	600 x 570 x 600	1100 x 570 x 600
Pull-out shelves	1	2
Usable inner shelf height (mm)	1 x 495	2 x 495
Door(s)	1	2
Weight (kg)	35	65
<b>Door hinge</b>		
<b>Article no., outer body:</b>	<b>left</b>	<b>B80-2859-A</b>
<b>RAL 7035 - light grey</b>	<b>right</b>	<b>B80-2860-A    B80-2823-A</b>
<b>Accessories</b>		
	<b>Article no.</b>	<b>Article no.</b>
Extra pull-out shelf as 2nd storage level	<b>B80-2824-A</b>	<b>B80-2868-A</b>
Socle height 35 mm	<b>B80-2825-A</b>	<b>B80-2869-A</b>

## SLS - CABINETS - WIDTH 600 MM AS PER TRGS 526 / DGUV

### For storage of acids and alkalis

- ◆ Body made from HPL-coated sheets - particularly impact, scratch and abrasion proof
- ◆ Color RAL 7035 - light grey
- ◆ Inner body / inner fittings completely made from corrosion-proof components
- ◆ Doors with separate cylinder locks
- ◆ Marking according to ASR A1.3
- ◆ Leveling feets for installing cabinet horizontally
- ◆ With central horizontal division for storage of acids and alkalis in separate compartments
- ◆ Supply air by ventilation grille in the back wall
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof

### With inner fittings:

- ◆ Pull-out shelves (to full extent) with end stop
  - Max. load 20 kg / shelf
  - Front edge of shelves in attractive solid wood design
  - PE sump tray (sump capacity 20 liters) on shelf secured against slipping - easy to remove
  - Model SLS 600 GL/3-SF3 additionally with full extent pull-out drawers with built-in PE sump trays (sump capacity 20 liters)



**SLS 600 GL/6,**  
**Article no. B80-3014-D**

**SLS 600/4,**  
**Article no. B80-3010-D**

**SLS 600 GL/3-SF3,**  
**Article no. B80-3020-D**

Model	SLS 600/4	SLS 600/6	SLS 600 GL/4	SLS 600 GL/6	SLS 600 GL/3-SF3
External dimension W x D x H (mm)	600 x 600 x 1935	600 x 600 x 1935	600 x 600 x 1935	600 x 600 x 1935	600 x 600 x 1935
Pull-out shelves	2 x 2	2 x 3	2 x 2	2 x 3	3
Usable inner shelf height (mm)	4 x 420	4 x 275 / 2 x 248	4 x 420	4 x 275 / 2 x 248	2 x 275 / 1 x 248
Drawers	-	-	-	-	3
Usable inner drawer height (mm)	-	-	-	-	1 x 255 / 1 x 275 / 1 x 250
Doors	2	2	2 (acrylic glass doors)	2 (acrylic glass doors)	1 (acrylic glass door)
Weight (kg)	110	116	110	116	116
<b>Door hinge</b>					
<b>Article no., outer body:</b>	<b>left</b>	<b>B80-3010-D</b>	<b>B80-3012-D</b>	<b>B80-3018-D</b>	<b>B80-3014-D</b>
<b>RAL 7035 - light grey</b>	<b>right</b>	<b>B80-3011-D</b>	<b>B80-3013-D</b>	<b>B80-3019-D</b>	<b>B80-3015-D</b>
<b>Accessory</b>					
		<b>Article no.</b>			
Pull-out shelf		<b>B80-2824-A</b>			