




Explanations see practical informations on page 6 and 84!

SIS TYPE 90 / 1200 VS WITH PULL-OUT SHELVES AS PER DIN EN 14470-1 (TYPE 90)

Approved for storage of flammable liquids at the workplace as per DIN EN 14470-1 (type 90) and TRGS 510, annex 1

- ◆ Whole construction tested and approved by an authorized materials testing institute as per DIN EN 14470-1 (type 90) with a fire resistance > 90 minutes
- ◆ Insulation according to DIN 4102
- ◆ Outer body made from powder-coated sheet steel, RAL 7035 - light grey, doors either in RAL 7035 - light grey or RAL 1007 - daffodil yellow
- ◆ Inner body made from HPL-coated sheets - RAL 7035
- ◆ Stainless steel base plate - Niro Rhombus
- ◆ Pull-out shelves with automatic return ensure high working safety
- ◆ Automatic thermal closing mechanism if fire occurs
 - Doors after temperature increase to ≤50°C and
 - Inlet and outlet channels after temperature increase to 70°C (±10°C)
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof
- ◆ Operation complies with TRGS 510 (approved even without exhaust air connection!)
- ◆ Ground connection in accordance with TRBS 2153 (avoidance of sources of ignition)
- ◆ Markings according to DIN EN 14470-1 / TRGS 510 / ISO 3864 / ASR A1.3
- ◆ Leveling feet for installing cabinet horizontally
- ◆ Doors with cylinder lock




SiS Type 90 / 1200 VS6, Article no. B80-2534-B, RAL 7035, incl. 6 pull-out shelves

With inner fittings:

- ◆ Either with 6, 5 or 4 pull-out shelves (AZW)* as per WHG - **Ü-sign according to StawaR**
- ◆ **door hold-open device**

* max. load 30 kg per shelf with uniformly distributed load



Model	SiS Type 90 / 1200 VS6	SiS Type 90 / 1200 VS5	SiS Type 90 / 1200 VS4
External dimensions W x D x H (mm)	1190 x 598 x 1935	1190 x 598 x 1935	1190 x 598 x 1935
Internal dimensions W x D x H (mm)	1087 x 430 x 1740	1087 x 430 x 1740	1087 x 430 x 1740
Doors	2	2	2
Inner fittings / Sump capacity (l)	6 x AZW / 6 x 17	5 x AZW / 5 x 17	4 x AZW / 4 x 17
Weight (kg)	522	514	506
Outer body: RAL 7035 - light grey	Material inner fittings		
Article no., doors: RAL 7035 - light grey	sheet steel	B80-2534-B	B80-2538-B
Article no., doors: RAL 1007 - daffodil yellow	sheet steel	B80-2536-G	B80-2540-G

Accessories	Material	Article no.
Perforated cover plate for pull-out shelf	sheet steel	B80-2546-B



SIS TYPE 90 / 1200 VS / ES WITH PULL-OUT SHELVES AS PER DIN EN 14470-1 (TYPE 90)


Approved for storage of flammable liquids at the workplace as per DIN EN 14470-1 (type 90) and TRGS 510, annex 1

- ◆ Whole construction tested and approved by an authorized materials testing institute as per DIN EN 14470-1 (type 90) with a fire resistance > 90 minutes
- ◆ GS-approved safety (GS-sign)
- ◆ Insulation according to DIN 4102
- ◆ Outer body made from powder-coated sheet steel, RAL 7035 - light grey, doors either in RAL 7035 - light grey or RAL 1007 - daffodil yellow
- ◆ Inner body made from HPL-coated sheets - RAL 7035
- ◆ Stainless steel base plate - Niro Rhombus
- ◆ Pull-out shelves with automatic return ensure high working safety
- ◆ Tray-shaped shelves height-adjustable at intervals of 64 mm
- ◆ Automatic thermal closing mechanism if fire occurs
 - Doors after temperature increase to ≤50°C and
 - Inlet and outlet channels after temperature increase to 70°C (±10°C)
- ◆ DN 80 ventilation connection for exhaust air extraction on cabinet roof
- ◆ Operation complies with TRGS 510 (approved even without exhaust air connection!)
- ◆ Ground connection in accordance with TRBS 2153 (avoidance of sources of ignition)
- ◆ Markings according to DIN EN 14470-1 / TRGS 510 / ISO 3864 / ASR A1.3
- ◆ Leveling feet for installing cabinet horizontally
- ◆ Doors with cylinder lock


With inner fittings:

- ◆ Either with base sump tray (BW), perforated cover plate (LB) and tray-shaped shelves (EN), pull-out shelves (AZW)*, disposal compartment (ESF) as per WHG - **Ü-sign according to StawaR**
- ◆ With central dividing panel
- ◆ **door hold-open device**

* max. load 30 kg per shelf with uniformly distributed load



SiS Type 90 / 1200 ES MI, Article no. B80-2556-B, RAL 7035, incl. 6 pull-out shelves (left), 3 pull-out shelves and 1 disposal compartment (right)



Model	SiS Type 90 / 1200 VS MI	SiS Type 90 / 1200 VS MI	SiS Type 90 / 1200 ES MI	SiS Type 90 / 1200 ES MI
External dimensions W x D x H (mm)	1190 x 598 x 1935	1190 x 598 x 1935	1190 x 598 x 1935	1190 x 598 x 1935
Internal dimensions W x D x H (mm)	1087 x 430 x 1740	1087 x 430 x 1740	1087 x 430 x 1740	1087 x 430 x 1740
Doors	2	2	2	2
Inner fittings / Sump capacity (l)	Dividing panel		Dividing panel	
	left: 6 x AZW / 6 x 7 right: 6 x AZW / 6 x 7	left: 6 x AZW / 6 x 7 right: 3 x EN 1 x BW / 1 x 22 1 x LB	left: 6 x AZW / 6 x 7 right: 1 x ESF / 1 x 22 3 x AZW / 3 x 7	left: 1 x ESF / 1 x 22 3 x AZW / 3 x 7 right: 1 x ESF / 1 x 22 3 x AZW / 3 x 7
Weight (kg)	532	521	529	526
Outer body: RAL 7035 - light grey	Material inner fittings			
Article no., doors: RAL 7035 - light grey	sheet steel	B80-2548-B	B80-2552-B	B80-2556-B
Article no., doors: RAL 1007 - daffodil yellow	sheet steel	B80-2550-G	B80-2554-G	B80-2558-G

Accessories	Material	Article no. (Model VS)	Article no. (Model ES)
Perforated cover plate for pull-out shelf	sheet steel	B80-2582-B	B80-2582-B
Perforated cover plate for disposal compartment	sheet steel	-	B80-2594-B